



TASER® C2 CARTRIDGE SPECIFICATION



WARNING
 Electronic Control Device
 • Can temporarily incapacitate target.
 • Can cause injury.
 • Obey warnings, instructions and all laws.
 • Comply with current training materials and requirements.
 • See www.TASER.com.

TASER C2 Cartridge

| Model | Model No. | Propellant | Range ⁵ | Color |
|--------------------------------|-----------|----------------------------------|--------------------|-------|
| TASER C2 CARTRIDGE – TWO PACK | 37215 | Compressed Nitrogen ⁴ | 15' [4.57 m] | Black |
| TASER C2 CARTRIDGE – FOUR PACK | 37415 | Compressed Nitrogen ⁴ | 15' [4.57 m] | Black |

Specifications³

- Housing: High impact black polymer
- Shelf life: 5 years
- Environmental:
 Temperature range: -20 °C to +50 °C
 Relative Humidity: 15% to 80%
 Storage Temperature: -40 °C to +65 °C

Features

- Reversible cartridge installation.
- Anti-Felon Identification (AFID) tracking system with serialized microdots.
- Can function in drive-stun capability after cartridge deployment without removing the cartridge from the TASER C2 firing bay.
- When a TASER C2 Cartridge is deployed, 20 to 30 small confetti-like Anti-Felon Identification (AFID) tags are deployed, allowing law enforcement agencies to determine the registered owner of the cartridge and track citizen use if ever used in a criminal act.
- Replaceable TASER C2 Cartridge contains compressed nitrogen to deploy two small probes that are attached to the TASER C2 Cartridge by insulated conductive wires.

Dart Grouping^{1,7}

| Model | Dart | 4' [1.22 m] | 8' [2.44 m] | 12' [3.66 m] | 15' [4.57 m] |
|----------|--------|-----------------|------------------|------------------|-----------------|
| Distance | Spread | | | | |
| 15' | Top | 1.89" [4.8 cm] | 2.15" [5.5 cm] | 1.29" [3.3 cm] | 0.00" [0.0 cm] |
| | Spread | 7.64" [19.4 cm] | 13.52" [34.3 cm] | 19.55" [49.7 cm] | 24.60" [62.5cm] |

Physical Dimensions^{1,3}

| Dimensions | | | | Dimensions (Installed on C2) |
|-----------------|-------------------|-------------------|-------------------|------------------------------|
| Length (L) | Height (H) | Width (W) | Weight | Length (L) |
| 2.00" [5.08 cm] | 1.485" [3.772 cm] | 1.132" [2.875 cm] | 1.32 oz [37.42 g] | 6.00" [15.24 cm] |
| | | | | |

- Dimensions are in English [Metric].
- Additional terms and conditions may apply (For additional information contact a TASER International sales representative or visit online at www.TASER.com).
- Product specifications may change without notice; actual product may vary from the picture.
- Material Safety Data Sheet (MSDS) related to nitrogen gas charged cartridges is available upon request.
- Actual wire length may be up to 6" longer.
- For additional cartridges, contact TASER International sales representatives.
- Dart grouping distances are averages measured in correlation to the laser dot projection at specified distance, test performed at ambient temperature [70 °F (25 °C)], results listed are averaged ± 0.50 " [1.27 cm]. "Spread" is the average measurement from the top dart to the bottom dart.
- TASER C2 Cartridges available only in 15' [4.57 m] range. Use of cartridges not authorized by TASER International will void the product warranty.
- The TASER C2 Cartridge will only work with a TASER C2 electronic control device, and is not interchangeable with any other TASER brand device.
- TASER is a registered trademark in the United States, Hong Kong, China, Japan, Rep. of Korea, Singapore, South Africa, OHIM, and Taiwan R.O.C. The bolt on circle logo is a trademark of TASER International, Inc. All rights reserved. U.S. patents 5078117, 6999295, 7075770, 7102870, 7145762, 7218077, 7234262, and other patents pending.
- As with all TASER International, Inc. products read, understand, and follow all warnings and training materials prior to handling or use.